

## DRML / DRMR | Running Man Left / Right Installation

Final exit door shall be marked with a low location luminous emergency exit symbol complying with NFPA 170. These are commonly known as the "running man". The symbol shall be mounted on the door centered horizontally, with the top of the symbol no higher than 18 inches (457 mm) above the floor.



For compliant placement of running man symbol, consult your applicable local or national codes (2009, 2012 IBC section 1024 + 2015 IBC section 1025).

## The running man must face the direction of travel.

## **Installation Steps:**

1. Thoroughly clean the surface area where the sign will be installed using isopropyl alcohol and a clean dry cloth to remove any loose particles, grease or dirt. Surface must be dry and dust free.

2. Peel the backing from the sign and apply firmly to surface without touching the adhesive.

**Maintain** by cleaning as necessary with cloth and/ or mild non-abrasive cleaner if needed.



## **Photo-Glo Charge Instruction:**

Minimum of 1-foot candle (11 Lux) of fluorescent, incandescent or LED (light emitting diode) for 60 minutes is required to charge Photo-Glo.

Control of lighting restricted to authorized personnel. Reliable external illumination is required at all times during occupancy.

Do not use Photo-Glo where ambient illumination level is less than 1-foot candle (11 Lux)

If you have further questions, please contact us:

Call: 1-855-723-6673 Email: sales@safetnose.com